

▼ Pendant & Ball Speakers

Redback® 30W 100V Line Pendant Ball Speaker

A stylish pendant speaker for installations requiring a high power & SPL output. Ideally suited to high raked, suspended, concrete or exposed ceilings. Installation requires a single fixing with connection concealed within the ceiling rose provided. Fitted with 6.5" coaxial 2 way driver and high efficiency transformer. The excellent frequency response and power output is ideal for background music in retail stores, restaurants, bars and function venues.



Features • Wide frequency response • High speech intelligibility • Fitted with 2m cable and ceiling rose • Stylish modern finish • 6.5" coaxial speaker • Ideal for BGM and paging requirements

SPECIFICATIONS

| | |
|-----------------|--------------------|
| Power: | 30W RMS |
| Power taps: | 3.8, 7.5, 15 & 30W |
| SPL 1W @ 1m: | 90dB |
| Freq. response: | 50Hz - 20kHz |
| Weight: | 2kg |
| Dimensions: | 252Ø x 240Hmm |

| Price Each | RRP | 3+ |
|---------------|---------------|---------------|
| C 1060 | 172.00 | 160.00 |

Redback® 30W 100V Line Slim Pendant Ball Speaker

Designed for use where traditional ceiling mounted speakers are difficult or impractical to install. Used in such areas as very high raked, suspended, concrete, or exposed ceilings. Installation requires a single fixing with connection concealed within the ceiling rose provided. This model is fitted with a high efficiency 114mm (4.5") full range 30W driver, fitted with internal 100V line transformer with an 8 Ohm bypass.



Features • Constructed from white ABS plastic • Wide frequency response • High speech intelligibility • Fitted with 3m cable and ceiling rose • Stylish modern finish • 4.5" speaker • Ideal for BGM and paging requirements

SPECIFICATIONS

| | |
|---------------------|------------------------|
| Power Taps: | 5, 10, 15, 20, 30W, 8Ω |
| SPL: | 1W @ 1m: 90dB |
| Frequency Response: | 70Hz - 20kHz |
| Weight: | 2.1kg |
| Cable Length: | 3m |
| Dimensions: | Ø185mm x 230mm |

| Price Each | RRP | 3+ |
|---------------------|---------------|---------------|
| C 1057 White | 215.00 | 202.00 |
| C 1058 Black | 229.00 | 219.00 |

▼ Sound Projectors

Redback® 20W 100V Line IP65 Rated Sound Projector (EWIS)**Now includes 22µF capacitor for line monitoring applications.**

The Redback® sound projector is made from strong UV stabilised ABS plastic with a perforated metal grille. It is designed for use in 100V line distributed systems. A wide dynamic range facilitates use with both paging and background music applications eg: sports stadiums, train station platforms, shopping centres, aquatic arenas, etc.



Features • Tough UV stabilised high impact ABS construction • Durable powdercoated mounting bracket • Stainless steel fixings • Exceptional music and speech reproduction • Selectable power taps • Uses a high efficiency driver and line transformer • Suitable for indoor or outdoor use • Includes 7-core cable for easy power tap selection

SPECIFICATIONS

| | |
|---------------------|------------------|
| Power taps: | 2.5, 5, 10 & 20W |
| SPL 1W @ 1m: | 92dB |
| Frequency response: | 110Hz - 18kHz |
| Dimensions: | ≈138Ø x 195D mm |
| Weight: | 1.9kg |

| Price Each | RRP | 2+ |
|---------------------------------|---------------|---------------|
| C 1520 White | 160.00 | 149.00 |
| C 1549 Black NEW! | 190.00 | 170.00 |

Redback® 20W 100V IP65 Bi-Directional Sound Projector (EWIS)

This bi-directional speaker is manufactured from a heavy duty aluminium extrusion. It is fitted with two high efficiency 5" speaker drivers offering exceptional speech intelligibility. Housing & grille are finished in industrial grade white powdercoat, while each speaker cone is treated to withstand moisture. A low profile aluminium mounting bracket is fitted to the housing. Applications include train stations, airports, carparks, schools, office corridors etc. Fitted with 22µF capacitor for line monitoring.



Features • Tough aluminium extrusion construction • Aluminium grille • Concealed tamper resistant mounting bracket • Weather-proof IP65 rated • Includes 5 core cable for easy power tap selection • Fitted with 22µF capacitor for line monitoring

SPECIFICATIONS

| | |
|---------------------|------------------|
| Power taps: | 2.5, 5, 10 & 20W |
| SPL 1W @ 1m: | 92dB |
| Frequency response: | 120Hz - 18kHz |
| Dimensions: | 140Ø x 200D |
| Weight: | ≈3.1kg |

| Price Each | RRP | 2+ |
|---------------|---------------|---------------|
| C 1522 | 215.00 | 195.00 |

Redback® One-Shot 20W 100V Fire Sound Projector**NEW!**

Twist lock cap makes internal termination easy! Saving you time and money.
Patent/registered design pending.

Approved for use in fire & evacuation systems in Australia (AS ISO 7240.24:2015).

Our first One-Shot sound projector, designed to save installers time and money. Typically to terminate cabling internally on a horn speaker it involves removing three screws on the rear cover, connecting the cable and then re-installing the same screws. As you can imagine, doing this up a ladder can get quite fiddly! The One-Shot eliminates screw removal by utilising a patented twist lock mechanism. The installer simply twists off the rear cover, connects the cabling and twists the cover back on! The labour savings by using the One-Shot on a large job are significant.

To make it even easier, we've also incorporated our patented dog leg mounting bracket which eliminates the need to separate the housing from the bracket during installation.

This sound projector is primarily used for fire and evacuation systems where a high degree of speech articulation and program clarity is paramount. Typical applications include schools, train and bus stations, airports, car parks and plant rooms.

Features • Weather resistant • UV stabilised plastic for long life even full sun • Durable powdercoated mounting bracket • Stainless steel fixings • Flame retardant • Designed to meet AS ISO7240.24 for fire & evacuation installations

SPECIFICATIONS

| | |
|---------------------|------------------|
| Power taps: | 2.5, 5, 10 & 20W |
| SPL 1W @ 1m: | 92dB |
| SPL Max Tap @1m: | 102dB |
| Frequency response: | 180Hz - 12kHz |
| Dimensions: | ≈147Ø x 215D mm |
| Weight: | 2.2kg |

| Price Each | RRP | 2+ |
|----------------------|---------------|---------------|
| CF1520G Grey | 145.00 | 135.00 |
| CF1520B Black | 150.00 | 140.00 |
| CF1520W White | 150.00 | 140.00 |

New Items

Please note that some items marked as "new" may not be available when the catalogue is released. For these items, we suggest you contact us for stock availability before ordering